

IMPROVED KING PIN NUT FOR SKATEBOARD APPLICATIONS

5

BACKGROUND OF THE INVENTION

Field of the Invention

10

The present invention relates to fasteners, and more particularly to an improved nut for use with a king pin used for affixing wheel trucks to skateboards.

Description of the Related Art

00755615-0140020

Skateboards are commonly used for recreation and competition purposes. Conventional skateboards comprise an elongated board supported on two spaced-apart wheel trucks comprising two wheels each mounted to the underside of the elongated board. Skateboard trucks may further utilize a high performance king pin for attaching a skateboard truck to a baseplate. The elongated board is constructed of a high impact, resilient and durable material such as a wood laminate or the like, on which the skateboard rider balances himself and adjusts the direction of travel by adjusting the pressure of his weight at various locations on the board.

25

Generally, the turning of a skateboard during use is accomplished by a shifting of the rider's weight to an off-center position on the supporting platform so as to cause a torquing movement about the various supports. As a result, the supporting bushings are compressed or torqued such that the resolution of forces about the axes of the various support members causes the truck axles to rotate about more or

less determinable axes angularly intersecting the supporting platform and as a result causing each truck wheel set to turn relative to the longitudinal axis of the supporting surface. However, in most cases, the turning action is nonuniform and nonreproducible because different variations of side loading cause different angular orientations of the truck axles, and conversely, different reductions in side loading cause different restoring forces to be applied to the truck axles.

During use, the skateboard typically experiences very high shear and compression loads that are placed upon the resilient elements with the result that their useful life is quite limited. This occurs since turns are effected by compressing or otherwise stressing one or more blocks of resilient material, whereby the restoring force is more or less proportional to the angle of turn, and as a consequence where the rider attempts to maintain a sharp turn he must continuously exert a substantial force against what is usually a strong restoring force. As a result, a shift in weight allows the restoring force to change the turning angle of the truck, and this severe cycling of stresses causes wear to and between the various truck components.

More particularly, a disadvantage of the prior art truck configuration is that very high shear and compression loads are placed upon the resilient elements with the result that their useful life may be limited, and consequently, the trucks must be disassembled from the skateboard to enable replacement of the kingpin, bushings, and other related components. That is, the king pin is placed under significant loadings during severe use of the skateboard, causing the king pin securing nut to loosen and in turn allowing for vibratory damage to occur between the king pin and the bore and truck components in which it is installed. In addition, the various

components tend to be fabricated of aluminum alloys, all of which are prone to wear, in turn causing the trucks to wobble over time.

Accordingly, due to these tremendous forces exerted upon the skateboard and consequential wear, it is desirable to be able to remove the trucks, wheels, and other components for repair or replacement on a periodic basis. According to the related art, the axle of each skateboard truck is secured to the truck base bracket or baseplate by a king pin extending through a recess formed in each truck.

However, an important shortcoming of the fastener of the prior art is the absence of suitable gripping surfaces on the fastener the carriage bolt or king pin concealed within the truck, which thereby prevents a positive disengagement against the attachment hardware when a wrench is applied to a fastener at the underside of the elongated board, for securing the truck or other component to the underside of the board.

Moreover, a plurality of fastener components are required to reassemble each truck to the skateboard, thus requiring the concurrent application of two hand tools, and oftentimes inappropriate tools are applied to the bolt head in an effort to loosen or tighten the carriage bolt or king pin and provide the necessary amount of torque. Moreover, the prior art carriage bolt or king pin is known to shift and rotate during removal and installation as well as when the skateboard is being ridden by impact and vibration, thus causing internal wear and tear of the elongated board and possibly shortening the life of the elongated board.

Summary of the Invention

Accordingly, it is an object of the present invention to provide an improved king pin nut for securing a skateboard axle bracket to its supporting baseplate in a skateboard application, the fastener providing a secure attachment system while enabling ready removal of selected components without damage to the skateboard or truck during removal and replacement.

Another object of the present invention is to provide a fastener having greater torque capacity and yet is readily secured to the skateboard, especially over a period of time and use.

Yet another object of the present invention is to provide a fastener that is simple and inexpensive to manufacture, and is interchangeable with complementary fasteners of the related art.

These and other object and advantages are obtained with an improved king pin nut for use with a king pin, such as a grinding king pin, in a skateboard truck assembly. The king pin nut of the present invention includes an elongated generally cylindrical nut that is internally threaded for receiving the threaded shaft of the truck king pin. The king pin nut includes a shoulder extending from an intermediate portion of the periphery of the elongated nut, the shoulder having a configuration complementary to a receiving recess provided in the truck base bracket to which a truck axle bracket is to be assembled. When the king pin is assembled to the truck base bracket to secure the truck axle bracket between a pair of constraining resilient bushings, the king pin is secured to the truck simply by

application of a tool to the head of the king pin which is threaded into the improved nut which is secured against rotation when its shoulder is positioned in the appropriate receiving bracket in the truck baseplate. As a benefit of the invention, the bore provided in the truck base bracket for receiving the king pin is enlarged in comparison to the related art, and a substantial longitudinal extent of the shaft of the king pin is secured within and carried by the elongated body of the cylindrical nut, thereby protecting the king pin against abrasion in the installed condition, unlike fastening systems of the prior art that are exposed to wear, vibration, and impact damage.

The invention will be better understood upon a reading of the following specification, read in conjunction with the accompanying drawings.

Brief Description of the Drawings

Fig. 1 is a perspective view of a skateboard showing the relative position of the front and rear trucks and mounting arrangement therebetween.

Fig. 2 is an exploded view of the assembly of each truck shown in Fig. 1, further showing the improved king pin nut of the present invention positioned for fastening to a grinding king pin to secure the truck to a skateboard.

Fig. 3 is a bottom plan view of a truck baseplate, showing a recess for receiving a complementary-shaped shoulder of the improved king pin nut of the present invention.

Fig. 4 is a top plan view of the truck base bracket shown in Fig. 3.

Fig. 5(a) is a partial cross-section view of the truck base bracket shown in Fig. 3, showing the recess for receiving the complementary-shaped shoulder of the king pin.

Fig. 5(b) is a partial cross-section view of the truck base bracket shown in Fig. 3, showing the recess for receiving the complementary-shaped shoulder of the king pin, with an optional retainer pad shown in the installed position between the truck base bracket and the skateboard to which it is mounted.

Fig. 6 is a perspective view of the improved king pin nut of the present invention.

Detailed Description of the Invention

With reference now to the drawings, and according to the present invention, Fig. 1 illustrates a skateboard 10 supported on two spaced-apart wheel trucks 12 to be securely mounted to the underside 14 of the skateboard 10. Each wheel truck 12 supports for rotation two wheels 16 each mounted to an axle 17 (Fig. 2). The axle 17 is secured in an axle bracket 18, which is secured to a truck baseplate 20 by a king pin 22 extending thereto and secured by the improved king pin nut 30 of the present invention. The king pin 22 may be a grinding king pin as will be appreciated by the skilled artisan. Each truck 12 is affixed to the underside 14 of the skateboard 10 utilizing a plurality of fasteners 32.

With reference now to Figs. 3-6, the king pin nut 30 of the present invention

includes an elongated generally cylindrical body 34 having a coaxial bore 36 formed therein. According to one embodiment, the king pin nut 30 is internally threaded as by drilling and tapping of the cylindrical body 34. Alternatively, a threaded nylon locking bushing 38 may be received and secured in the coaxial bore 36. According to either embodiment, a threaded shaft 40 of the king pin 22 is received therein in threaded engagement.

The king pin nut 30 includes a shoulder 42 extending from an intermediate portion of the periphery of the cylindrical body 34 of king pin nut 30, the shoulder 42 having a configuration complementary to a receiving recess 44 provided in the baseplate 20 to which a truck axle bracket 18 is to be assembled. A bore 45 extending from the receiving recess 44 to a top face 47 of the base plate is configured to receive the shoulder 42 of the king pin nut 30 in the fully installed condition. The king pin nut 30 is fabricated of mild steel, although other strong, durable materials may be utilized to meet the demands of this application.

King pin nut 30 is assembled to the underside of base plate 20 after removing base plate 20 from the underside 14 of skateboard 10. The cylindrical body 34 of the king pin nut 30 is extended into the receiving recess 44 and then into the bore 45 a sufficient distance to cause the shoulder 42 to become lodged within recess 44 (Figs. 4, 5). This position is assured when the base plate 20 is reassembled to the skateboard, such that the king pin nut 30 is captivated between the baseplate 20 and the underside 14 of the skateboard with at least a portion of the shoulder 42 contained within the receiving recess 44, preventing counter-rotation of the king pin nut 30 when king pin 22 is threaded into and fully engaged with the king pin

nut 30, in the manner to be described below.

According to another embodiment, a riser pad 100 (Figs. 2 and 5(b)) may be provided between the underside of the baseplate 20 and underside 14 of skateboard 10. The retainer pad 100 provides a shock absorbing function between the skateboard and the baseplate 20, further having an opening 102 through which the installed king pin 22 and king pin nut 30 may project to suspend the king pin nut 30 in the desired position prior to installation and tightening of the king pin 22 to the baseplate 20. Riser pad 100 may have a polymeric or other construction, and conforms with the contours of the undersurface of the baseplate 20 to bring the baseplate, riser pad 100 and skateboard 10 into a substantially tightly aligned and sealed assembly when the king pin 22 is fully secured to the king pin nut 30. The retainer pad 100 further includes openings 104 through which fasteners (not shown) may be projected to secure the baseplate 20 to skateboard 14 while securing the retainer pad 100 against lateral displacement therebetween.

It will be appreciated by the skilled artisan that although the shoulder 42 of the preferred embodiment is shown with a substantially square profile, other configurations of the shoulder 42 may be employed to either conform with a standard square opening provided in the baseplate 20, or to conform with an opening of a different configuration.

Subsequent to the installation of the king pin nut 30, the king pin 22 is assembled to the truck baseplate 20 by threading the truck axle bracket 18 via recess 18(a)

between a pair of constraining resilient bushings 46, 48 and washer 50. The king pin 22 is further extended through receiving recess 44 simply by application of the appropriate tool to the head of the king pin.

- 5 It will be appreciated that removal of the various components may be readily achieved by reversing the above described steps, with the assurance that the king pin 22 can be later reassembled using a single wrench or driver. It will be further appreciated that the present invention may be utilized to secure accessories including the baseplate 20 to the skateboard 10, whether to the underside 14 thereof or to the top side. Such accessories may include, but are not limited to, bumpers, stops, handles or other items associated with the use, storage and repair of skateboards. It will also be appreciated that the fastener of the present invention may be used to secure a wheel truck carrying a single or plural wheels to a support such as a skateboard or other structure or chassis.

10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990
1000
1010
1020
1030
1040
1050
1060
1070
1080
1090
1100
1110
1120
1130
1140
1150
1160
1170
1180
1190
1200
1210
1220
1230
1240
1250
1260
1270
1280
1290
1300
1310
1320
1330
1340
1350
1360
1370
1380
1390
1400
1410
1420
1430
1440
1450
1460
1470
1480
1490
1500
1510
1520
1530
1540
1550
1560
1570
1580
1590
1600
1610
1620
1630
1640
1650
1660
1670
1680
1690
1700
1710
1720
1730
1740
1750
1760
1770
1780
1790
1800
1810
1820
1830
1840
1850
1860
1870
1880
1890
1900
1910
1920
1930
1940
1950
1960
1970
1980
1990
2000
2010
2020
2030
2040
2050
2060
2070
2080
2090
2100
2110
2120
2130
2140
2150
2160
2170
2180
2190
2200
2210
2220
2230
2240
2250
2260
2270
2280
2290
2300
2310
2320
2330
2340
2350
2360
2370
2380
2390
2400
2410
2420
2430
2440
2450
2460
2470
2480
2490
2500
2510
2520
2530
2540
2550
2560
2570
2580
2590
2600
2610
2620
2630
2640
2650
2660
2670
2680
2690
2700
2710
2720
2730
2740
2750
2760
2770
2780
2790
2800
2810
2820
2830
2840
2850
2860
2870
2880
2890
2900
2910
2920
2930
2940
2950
2960
2970
2980
2990
3000
3010
3020
3030
3040
3050
3060
3070
3080
3090
3100
3110
3120
3130
3140
3150
3160
3170
3180
3190
3200
3210
3220
3230
3240
3250
3260
3270
3280
3290
3300
3310
3320
3330
3340
3350
3360
3370
3380
3390
3400
3410
3420
3430
3440
3450
3460
3470
3480
3490
3500
3510
3520
3530
3540
3550
3560
3570
3580
3590
3600
3610
3620
3630
3640
3650
3660
3670
3680
3690
3700
3710
3720
3730
3740
3750
3760
3770
3780
3790
3800
3810
3820
3830
3840
3850
3860
3870
3880
3890
3900
3910
3920
3930
3940
3950
3960
3970
3980
3990
4000
4010
4020
4030
4040
4050
4060
4070
4080
4090
4100
4110
4120
4130
4140
4150
4160
4170
4180
4190
4200
4210
4220
4230
4240
4250
4260
4270
4280
4290
4300
4310
4320
4330
4340
4350
4360
4370
4380
4390
4400
4410
4420
4430
4440
4450
4460
4470
4480
4490
4500
4510
4520
4530
4540
4550
4560
4570
4580
4590
4600
4610
4620
4630
4640
4650
4660
4670
4680
4690
4700
4710
4720
4730
4740
4750
4760
4770
4780
4790
4800
4810
4820
4830
4840
4850
4860
4870
4880
4890
4900
4910
4920
4930
4940
4950
4960
4970
4980
4990
5000
5010
5020
5030
5040
5050
5060
5070
5080
5090
5100
5110
5120
5130
5140
5150
5160
5170
5180
5190
5200
5210
5220
5230
5240
5250
5260
5270
5280
5290
5300
5310
5320
5330
5340
5350
5360
5370
5380
5390
5400
5410
5420
5430
5440
5450
5460
5470
5480
5490
5500
5510
5520
5530
5540
5550
5560
5570
5580
5590
5600
5610
5620
5630
5640
5650
5660
5670
5680
5690
5700
5710
5720
5730
5740
5750
5760
5770
5780
5790
5800
5810
5820
5830
5840
5850
5860
5870
5880
5890
5900
5910
5920
5930
5940
5950
5960
5970
5980
5990
6000
6010
6020
6030
6040
6050
6060
6070
6080
6090
6100
6110
6120
6130
6140
6150
6160
6170
6180
6190
6200
6210
6220
6230
6240
6250
6260
6270
6280
6290
6300
6310
6320
6330
6340
6350
6360
6370
6380
6390
6400
6410
6420
6430
6440
6450
6460
6470
6480
6490
6500
6510
6520
6530
6540
6550
6560
6570
6580
6590
6600
6610
6620
6630
6640
6650
6660
6670
6680
6690
6700
6710
6720
6730
6740
6750
6760
6770
6780
6790
6800
6810
6820
6830
6840
6850
6860
6870
6880
6890
6900
6910
6920
6930
6940
6950
6960
6970
6980
6990
7000
7010
7020
7030
7040
7050
7060
7070
7080
7090
7100
7110
7120
7130
7140
7150
7160
7170
7180
7190
7200
7210
7220
7230
7240
7250
7260
7270
7280
7290
7300
7310
7320
7330
7340
7350
7360
7370
7380
7390
7400
7410
7420
7430
7440
7450
7460
7470
7480
7490
7500
7510
7520
7530
7540
7550
7560
7570
7580
7590
7600
7610
7620
7630
7640
7650
7660
7670
7680
7690
7700
7710
7720
7730
7740
7750
7760
7770
7780
7790
7800
7810
7820
7830
7840
7850
7860
7870
7880
7890
7900
7910
7920
7930
7940
7950
7960
7970
7980
7990
8000
8010
8020
8030
8040
8050
8060
8070
8080
8090
8100
8110
8120
8130
8140
8150
8160
8170
8180
8190
8200
8210
8220
8230
8240
8250
8260
8270
8280
8290
8300
8310
8320
8330
8340
8350
8360
8370
8380
8390
8400
8410
8420
8430
8440
8450
8460
8470
8480
8490
8500
8510
8520
8530
8540
8550
8560
8570
8580
8590
8600
8610
8620
8630
8640
8650
8660
8670
8680
8690
8700
8710
8720
8730
8740
8750
8760
8770
8780
8790
8800
8810
8820
8830
8840
8850
8860
8870
8880
8890
8900
8910
8920
8930
8940
8950
8960
8970
8980
8990
9000
9010
9020
9030
9040
9050
9060
9070
9080
9090
9100
9110
9120
9130
9140
9150
9160
9170
9180
9190
9200
9210
9220
9230
9240
9250
9260
9270
9280
9290
9300
9310
9320
9330
9340
9350
9360
9370
9380
9390
9400
9410
9420
9430
9440
9450
9460
9470
9480
9490
9500
9510
9520
9530
9540
9550
9560
9570
9580
9590
9600
9610
9620
9630
9640
9650
9660
9670
9680
9690
9700
9710
9720
9730
9740
9750
9760
9770
9780
9790
9800
9810
9820
9830
9840
9850
9860
9870
9880
9890
9900
9910
9920
9930
9940
9950
9960
9970
9980
9990
10000

It is to be understood that the present invention is not limited to the embodiments described above, but encompasses any and all embodiments within the scope of the following claims.